



Technical datasheet

E 24TC250



Brand	EREA
Article Number	E 24TC250
EAN-code Barcode	5414503003096
Code	2224
Product type	Single-phase control transformer
Primary Voltage	15-0-230-400V AC
Secondary Voltage	0-0-24V AC
Power	250 VA
Standards	EN 61558-2-2 EN 61558-2-6 EN 60742

General properties

Applications	For all applications, especially designed for inrush power in	Maximum ambient temperature t_a	50 °C
Protection class	Prepared for protection class II	Temperature class transfo	B
Degree of protection	IP20	Finishing	Vacuum-encapsulated with synthetic resin

Electrical properties


Frequency	50-60 Hz	Efficiency	91 %
Po	10,2 W	Pcu	15,4 W
Dielectric Strength	4500 Vac	Insulation resistance	200 MΩ
Dielectric strength referred to frame	-	Specific property	-
Voltage drop (dU%)	5,8 %	Short-circuit voltage (Ucc %)	5,3 %

Mechanical properties

Primary connection	Screw terminals 4 mm ²
Secondary connection	Screw terminals 4 mm ²
Fixation	Angle sections with fixing holes

Dimensions/weight

Dimensions AxBxC	102x102x110 mm
Dimension D	84 mm
Dimension E	86 mm
Dimension Ø	6 mm
Weight	3 kg



rev. 18.11.2020