



Technical datasheet

SPT50000/D/690



Brand	EREA
Article Number	SPT50000/D/690
EAN-code Barcode	5414503123763
Code	12376
Product type	Three-phase separating transformer
Primary Voltage	3x 690V Δ
Secondary Voltage	3 x 230V Δ -- 3x 400V Y+N
Power	50 000 VA
Standards	EN 60726 EN 60076

General properties

Applications	For industrial applications	Maximum ambient temperature ta	40 °C
Protection class	Prepared for protection class I	Temperature class transfo	F
Degree of protection	IP00	Finishing	Vacuum- and pressure- varnish impregnated

Electrical properties

Frequency	50-60 Hz	Efficiency	97 %
Po	285 W	Pcu	1078 W
Dielectric Strength	4500 Vac	Insulation resistance	200 MΩ
Dielectric strength referred to frame	2500 Vac	Specific property	Primary delta connected, secondary not connected
Voltage drop (dU%)	2,21 %	Short-circuit voltage (Ucc %)	-
Recommended fuse PRI	D80A (3x690V Δ)	Recommended fuse SEC	C125A (3x230V Δ) C80A (3x400V Y+N)

Mechanical properties


Primary connection	Nut fixing M10
Secondary connection	Nut fixing M10
Fixation	Supports with fixing holes

Protection case

Housing IP20	U 2222723
Housing IP23	K23EI500/001
Housing IP44	K44EI500/010

Dimensions/weight



Dimensions AxBxC	640x360x500 mm
Dimension D	400 mm
Dimension E	180 mm
Dimension Φ	11 mm
Weight	200 kg







Connection diagram SPT50000/D/690

3x 690V Δ → 3 x 230V Δ



3x 690V Δ → 3x 400V Y+N





Accessories SPT50000/D/690

IP20 housing

U 2222723



IP23 housing

K23EI500/001



Vibration damper

(4 pieces needed per transformer)

Silent block 75



rev. 29.07.2021